

TLM-1506 TFT LCD Monitor Preliminary Specification:

DESCRIPTION		MODEL	TLM-1506
LCD Panel	Screen Size	15 inch (diagonal)	
	Viewable size	304.1mm (H) x 228.1mm(V)	
	Dot Pitch	0.297mm x 0.297mm	
	View angle H/V	140(H)/125(V)	
	Contrast ratio	500:1	
	Brightness	450 cd/m ²	
	Resolution	1024 x 768	
	Response Time	8ms	
	Display Color	16.2M	
Control key define		Channel, Menu, -, +, Power	
Power Supply	Input-Voltage	100~240V _{AC}	
	Consumption	32W max.	
Video	Input	Composite video, connector: 1 BNC S-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω	
	Output	1 BNC connector for CVBS loop-through output,	
	OSD	Contrast, Brightness, Color, Tint, Sharpness, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit	
	System Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz	
Analog VGA	Input	Analog RGB: 0.707Vp-p / 75Ω, connector: 15 pin D-Sub	
	OSD	Brightness, Contrast, Display Adjust, Color Temperature, Language, OSD Adjust, Audio Control, Input Select, Reset, Exit	
	Plug & Play	DDC2B	
	Power Management	VESA DPMS	
	Support timing	VESA VGA / SVGA / XGA	
Audio	Input/Output	connector: 2 x RCA connector Level: 1.0Vp-p / 1 Khz	
	Speaker	2W x 2 embedded	
Mechanical	Dimension	356x387x200mm (with base), 356x300x67mm (without base)	
	Weight	9.0lbs/4.1Kg(with base)	
Additional benefit		Rack mountable (19" standard rack, EIA-310-D) VESA mount 100x100mm ² RoHS compliant	

Note: The preliminary specification are subject to change without notice.